



OPERATING AND MAINTENANCE INSTRUCTIONS

MAINTENANCE OF FIBREGLASS WINDOW AND PATIO DOOR PRODUCTS

No Special procedures are required since fibreglass, glass, paint finish and other components are highly resistance to corrosion in any form.

Should you require long term original performance the following practice is recommended

It is recommended that the glass and frames should be washed occasionally with a non abrasive detergent solvent.

The rubber weather stripping should be sprayed about a year apart with clear silicone and wiped with a cloth for even coat to prolong elasticity and performance indefinitely.

It is recommended that pile weather stripping on windows / sliding doors be silicone sprayed about twice a year for smoother operation.

BASIC SINGLE HUNG OPERATIONAL SUGGESTIONS:

Camlocks must be in a Fully open position before sliding sash up OR down

Interlock should be engaged prior to closing and lock sash into place.
A good seal will only be accomplished when the interlock is effectively engaged

Sash can be removed by tilting the sash inward and then lifting one side of the sash far enough to disengage. Reverse process for re-installation

THE ABOVE GUIDE LINES ARE FOR EXTENDED SUPERIOR PERFORMANCE

Sydney office:

Sovereign Windows & Doors Pty Limited
Unit 4 / 185 Briens Road
Northmead NSW
Australia 2152
ABN: 76 120 690 959

Phone: 02- 9630-8190
Fax: 02-9890-7133

Email: sales@sovereignwindows.com.au
Web site: www.sovereignwindows.com.au

